



Product Data Sheet - Nikki 1 Short Peak c/w 3 point chinstrap

Description

Nikki 1 Short Peak Hard Hat Ratchet
Lining c/w 3 point chinstrap (ABS)

Application

Head protection suitable for use in electrical environments and Working @ Height and other applications where improved upward visibility required.

Options

- Nikki 1 Short Peak Hard Hat Ratchet Lining with 3PT Chinstrap (generic) - Code: HHAT13201
- Nikki 1 Eskom Short Peak Hard Hat Ratchet Lining with 3PT Chinstrap - Code: NIKSP/03
- Available in a range of colours



Reference image with Eskom branding.

Key features

- Manufactured from lightweight ABS (Acrylonitrile Butadiene Styrene) offering superior rigidity, protection and durability.
- Inner of hard hat shell is engineered with reinforced ribs for increased protection against impact and lateral deformation.
- Designed to exceed the European standard (EN 397 : 1995) for Lateral Deformation. (Up to three times that of similar hard hats in the market).
- Turn top adjustable crown vent allows for double crown protection; it also allows for one hand adjustment to open for breathability or close for protection from chemical, liquids or falling gravel and rocks.
- Integrated slots that allow for the majority of accessories (earmuffs, face shields & visors).
- 4 point comfort ratchet lining for easy one-handed adjustment with Permasweat breathable sweatband and high visibility rear insert.
- Anti-glare peak.
- Ultra-violet inhibitor protects and extends life of helmet.
- Supporting ridge for cap attachment spring.
- Contoured rain channel allows liquid to run off front of peak rather than down neck and shoulders. Also provides additional lateral rigidity for more protection from lateral deformation. Ideal for high angle work situations.
- ARC rated and electrical insulation - tested to 18 CAL/CM² and 1000 volts dielectric.

Care and Maintenance

Nikki hard hats should be discarded after 5 years from date of manufacture (as per manufacturing date stamp in every hard hat), and after 2 years from date of first issue (as per details in each hard hat label). Please note this is a guideline subject to hard hats being properly stored before date of issue and during service period. Any hard hat subjected to impact or with visual damage should be discarded immediately. Full details are included on a label inside every Nikki hard hat, but to extend the service life of your hard hat:

- Never store a hard hat in direct sunlight and avoid exposure to extreme temperatures and chemicals.
- Remove dirt and stains from the shell and suspension system by scrubbing them with a mild detergent.
- Rinse the shell thoroughly with warm (not hot) water.
- Wipe the shell dry and carefully inspect the shell and the suspension systems for signs of wear and damage.

Standards

- Meets requirements of SANS 1397:2003.
- 18 Cal/cm² Tested against ASTM F2178 for Arc Flash protection (accompanied by recommended Face shield).
- Meets requirements of SANS 724:2009.
- Tested to 1000V rating.
- Government Mining Engineer approved for use in mines.
- SABS approved with Mark Scheme No. 6921.
- Made in South Africa.



Ratchet Lining




Short Peak



Long Peak

Colourways

Other colours available on request





Product Data Sheet - Nikki 1

Description

Nikki 1 hard hat for industrial and mining use made of ABS plastic

Application

Head protection for:

- Forestry
- Process industries
- Construction
- Mining
- Power generation
- Manufacturing
- Other general hard hat requirements.

Designed for maximum comfort, durability and protection in all-day use.

Key features

- Manufactured from lightweight ABS (Acrylonitrile Butadiene Styrene) offering superior rigidity, protection and durability.
- Inner of hard hat shell is engineered with reinforced ribs for increased protection against impact and lateral deformation.
- Designed to exceed the European standard (EN 397 : 1995) for Lateral Deformation. (Up to three times that of similar hard hats in the market).
- Turn top adjustable crown vent allows for double crown protection; it also allows for one hand adjustment to open for breathability or close for protection from chemical, liquids or falling gravel and rocks.
- Integrated slots that allow for the majority of accessories (earmuffs, face shields & visors).
- 4 point comfort ratchet lining for easy one-handed adjustment with Permasweat breathable sweatband and high visibility rear insert.
- Anti-glare peak.
- Ultra-violet inhibitor protects and extends life of helmet.
- Supporting ridge for cap attachment spring.
- Contoured rain channel allows liquid to run off front of peak rather than down neck and shoulders. Also provides additional lateral rigidity for more protection from lateral deformation. Ideal for high angle work situations.
- ARC rated and electrical insulation - tested to 18cal/cm2 and 1000 volts dielectric



Options



Colourways



Care and Maintenance

Exposure to temperature extremes, sunlight, or chemicals (such as fire retardant or tree-marking paint), shorten the lifespan of a hard hat.

Follow these practices to protect your hard hat and extend its service life:

- Never store a hard hat in direct sunlight.
- Remove dirt and stains from the shell and suspension system by scrubbing them with a mild detergent.
- Rinse the shell thoroughly with warm (not hot) water.
- Wipe the shell dry and carefully inspect the shell and the suspension systems for signs of wear and damage.

Product codes

- Nikki 1 Industrial Standard Lining:
HHAT11100
- Nikki 1 Industrial Ratchet Lining:
HHAT11200
- Nikki 1 Mining Standard Lining:
HHAT12100
- Nikki 1 Mining Ratchet Lining:
HHAT12200
- Nikki 1 Short Peak Industrial Ratchet Lining:
HHAT13200

Standards

- Meets requirements of SANS 1397:2003.
- 18 Cal/cm² Tested against ASTM F2178 for Arc Flash protection (accompanied by recommended Face shield).
- Meets requirements of SANS 724:2009.
- Tested to 1000V rating.
- Government Mining Engineer approved for use in mines.
- SABS approved with Mark Scheme No. 6921.
- Made in South Africa.





Product Data Sheet - Nikki 2

Description

Nikki 2 hard hat for industrial and mining use made of Polyprop Plastic



Application

Head protection for:

- Forestry
- Process industries
- Construction
- Mining
- Manufacturing
- Other general hard hat requirements.

Designed for maximum comfort, durability and protection in all-day use.

Key features

- Manufactured from lightweight Polyprop Plastic.
- Inner of hard hat shell is engineered with reinforced ribs for increased protection against impact and lateral deformation.
- Integrated slots that allow for the majority of accessories (earmuffs, face shields & visors).
- Designed to exceed the European standard (EN 397 : 1995) for Lateral Deformation.
- 4 Point standard shock absorption replaceable lining.

Options

- 4 Point comfort ratchet lining for easy one-handed adjustment with Permasweat breathable sweatband and high visibility rear insert.
- Mining option includes a bracket and cord holder.
- Available in open vent for breathability or closed vent for protection from chemical, liquids or falling gravel and rocks.
- Available in a range of colours.
- Anti-glare peak.
- Ultra-violet inhibitor protects and extends life of helmet.
- Supporting ridge for cap attachment spring.
- Contoured rain channel allows liquid to run off front of peak rather than down neck and shoulders. Also provides additional lateral rigidity for more protection from lateral deformation. Ideal for high angle work situations.



Mining Option, Closed Vent



Ratchet Lining



Standard Lining



Industrial Option, Closed Vent



Mining Option, Open Vent

Colourways



Care and Maintenance

Exposure to temperature extremes, sunlight, or chemicals (such as fire retardant or tree-marking paint), shorten the lifespan of a hard hat.

Follow these practices to protect your hard hat and extend its service life:

- Never store a hard hat in direct sunlight.
- Remove dirt and stains from the shell and suspension system by scrubbing them with a mild detergent.
- Rinse the shell thoroughly with warm (not hot) water.
- Wipe the shell dry and carefully inspect the shell and the suspension systems for signs of wear and damage.

Product codes

- Nikki 2 Industrial Closed Vent Standard Lining:
HHAT21110
- Nikki 2 Industrial Closed Vent Ratchet Lining:
HHAT21210
- Nikki 2 Mining Closed Vent Standard Lining:
HHAT22110
- Nikki 2 Mining Closed Vent Ratchet Lining:
HHAT22210
- Nikki 2 Industrial Open Vent Standard Lining:
HHAT21120
- Nikki 2 Industrial Open Vent Ratchet Lining:
HHAT21220
- Nikki 2 Mining Open Vent Standard Lining:
HHAT22120
- Nikki 2 Mining Open Vent Ratchet Lining:
HHAT22220

Standards

- Meets requirements of SANS 1397:2003 (Mark Scheme No. 6921).
- Government Mining Engineer approved for use in mines.
- Made in South Africa.





Product Data Sheet - Nikki 1 Eskom Hard Hat

Description

Nikki 1 Eskom Hard Hat RTC Lining c/w
3 point chinstrap made of ABS plastic



Application

Head protection suitable for use in electrical environments. Designed for maximum comfort, durability and protection in all-day use.

Options

- Nikki 1 Eskom Standard Hard Hat Ratchet Lining with 3PT Chinstrap - Code: NIKLP-03
- Nikki 1 Eskom Short Peak Hard Hat Ratchet Lining with 3PT Chinstrap - Code: NIKSP/03
- Available in a range of colours

Key features

- Manufactured from lightweight ABS (Acrylonitrile Butadiene Styrene) offering superior rigidity, protection and durability.
- Inner of hard hat shell is engineered with reinforced ribs for increased protection against impact and lateral deformation.
- Designed to exceed the European standard (EN 397 : 1995) for Lateral Deformation. (Up to three times that of similar hard hats in the market).
- Turn top adjustable crown vent allows for double crown protection; it also allows for one hand adjustment to open for breathability or close for protection from chemical, liquids or falling gravel and rocks.
- Integrated slots that allow for the majority of accessories (earmuffs, face shields & visors).
- 4 point comfort ratchet lining for easy one-handed adjustment with Permasweat breathable sweatband and high visibility rear insert.
- Anti-glare peak.
- Ultra-violet inhibitor protects and extends life of helmet.
- Supporting ridge for cap attachment spring.
- Contoured rain channel allows liquid to run off front of peak rather than down neck and shoulders. Also provides additional lateral rigidity for more protection from lateral deformation. Ideal for high angle work situations.
- ARC rated and electrical insulation - tested to 18 CAL/CM² and 1000 volts dielectric.

Care and Maintenance

Nikki hard hats should be discarded after 5 years from date of manufacture (as per manufacturing date stamp in every hard hat), and after 2 years from date of first issue (as per details in each hard hat label). Please note this is a guideline subject to hard hats being properly stored before date of issue and during service period. Any hard hat subjected to impact or with visual damage should be discarded immediately. Full details are included on a label inside every Nikki hard hat, but to extend the service life of your hard hat:

- Never store a hard hat in direct sunlight and avoid exposure to extreme temperatures and chemicals.
- Remove dirt and stains from the shell and suspension system by scrubbing them with a mild detergent.
- Rinse the shell thoroughly with warm (not hot) water.
- Wipe the shell dry and carefully inspect the shell and the suspension systems for signs of wear and damage.

Standards

- Meets requirements of SANS 1397:2003.
- 18 Cal/cm² Tested against ASTM F2178 for Arc Flash protection (accompanied by recommended Face shield).
- Meets requirements of SANS 724:2009.
- Tested to 1000V rating.
- Government Mining Engineer approved for use in mines.
- SABS approved with Mark Scheme No. 6921.
- Made in South Africa.



Ratchet Lining



Short Peak



Long Peak

Colourways

Other colours available on request

